

AUTOSTACKER™

A6S / A6SW

6,000-lbs. Capacity / Scissors Parking Lift Platform

The Autostacker is the latest-model parking lift to hit the home and commercial markets. With the strength to handle loads up to 6,000 lbs. and the minimal footprint necessary for a home garage lift, the Autostacker is the perfect garage parking lift for any home or shop owner.

Other mechanical parking systems can appear unsightly in home garages. Plus, most lifts feature four columns that obstruct access around the garage. Autostacker has no posts whatsoever, so it looks like it belongs anywhere you put it. We know that low-profile vehicles often struggle to safely load onto lifts without the help of pricey specialty ramps. Autostacker features a patented, inclined platform that accommodates low-stance vehicles with ease. Solve your car stacking problems with the world's smartest low-profile home parking lift.



6,000-lb. (2,722 kg) Lifting Capacity

WHAT'S INCLUDED

- Right & left side superstructure
- Front wheel trough
- Ramp assembly with logo plate
- Lower front tie-bar
- Galvanized decking sections
- Front tire stops
- Power unit control console
- Complete assembly parts package
- Installation and operators manual



1 Low-Profile Entry Ramp

7 Patented Door-Sentry™ car door protectors

6 Synchronizing flow control provides level lifting.

4 Tandem Direct-Drive Cylinders

5 Automatic Safety Locks

2 Wide Deck Platform

3 Tire Stop



SPECIFICATIONS & FEATURES

There are enough features and cool parking lift tweaks on Autostacker to keep you safer, happier and better cared for than with virtually any parking lift out there. Everything about the Autostacker screams, "Upgrade!" From the impressive lift capacity and superior drive-through clearance to the simple, post-free design that fits in most parking spaces, this is the parking lift you want with all the protection you deserve.

OPTION 1 Standard Console w/ Power Unit

SKU	MODEL	DESCRIPTION
5260591	A6S-OPT1	6,000 lb. Cap. Parking Lift / STANDARD / 208-240V, 50/60HZ, 1-Phase
5260298	A6S-OPT1-G	6,000 lb. Cap. Parking Lift / STANDARD / Galvanized / 208-240V, 50/60HZ, 1-Phase
5260592	A6W-OPT1	6,000 lb. Cap. Parking Lift / WIDE / 208-240V, 50/60HZ, 1-Phase
5260299	A6W-OPT1-G	6,000 lb. Cap. Parking Lift / WIDE / Galvanized / 208-240V, 50/60HZ, 1-Phase

OPTION 2 Fore Control Kit / Requires Master Power Unit (MPU)

SKU	MODEL	DESCRIPTION
5260304	A6S-OPT2	6,000 lb. Cap. Parking Lift / STANDARD / REQUIRES MPU
5260310	A6S-OPT2-G	6,000 lb. Cap. Parking Lift / STANDARD / Galvanized / REQUIRES MPU
5260319	A6W-OPT2	6,000 lb. Cap. Parking Lift / WIDE / REQUIRES MPU
5260354	A6W-OPT2-G	6,000 lb. Cap. Parking Lift / WIDE / Galvanized / REQUIRES MPU

OPTION 3 Aft Control Kit / Requires Master Power Unit (MPU)

SKU	MODEL	DESCRIPTION
5260595	A6S-OPT3	6,000 lb. Cap. Parking Lift / STANDARD / REQUIRES MPU
5260296	A6S-OPT3-G	6,000 lb. Cap. Parking Lift / STANDARD / Galvanized / REQUIRES MPU
5260596	A6W-OPT3	6,000 lb. Cap. Parking Lift / WIDE / REQUIRES MPU
5260297	A6W-OPT3-G	6,000 lb. Cap. Parking Lift / WIDE / Galvanized / REQUIRES MPU

Specifications

MODEL	A6S	A6W
Style	Standard	Wide
Overall Width	103" (2,616 mm)	111" (2,815 mm)
Overall Length	144" (3,658 mm)	144" (3,658 mm)
Platform Width	83.75" (2,127 mm)	91.75" (2,331 mm)
Platform Length	124" (3,150 mm)	124" (3,150 mm)
Ramp Height	2" (51 mm)	2" (51 mm)

POWER

Standard - Power Unit Console

- Single unit operation
- Motor Voltage: 208-240 VAC / 50/60Hz / 1Ph
- Power Consumption: 1,500 Watts
- Motor Horsepower: 2 HP
- Starting Amps: 25A
- Normal Running Amps: 12-18A

Optional - Master Power Unit

- Operates up to 14 lifts
- Motor horsepower: 7.5 HP
- Power consumption: 5,600 Watts
- Motor voltage: 208-230V/460 VAC, 50/60Hz / 3Ph
- Starting amps 208-230V: 25A
- Normal running amps 208-230V: 12-18A
- Starting amps 460V: 10A
- Normal running amps 460V: 6-9A

SPEED OF RISE

- **Standard power unit console:** 35 seconds
- **Optional multi-unit power unit console:** 20 seconds

